



| PRODUCTS | Püre Series | Décor Series | Lodge Series | Essential Series | Classics Series |
|-------------|--|----------------------------|---------------------|-----------------------------------|---------------------|
| Species | Red Oak, Hard Maple | Red Oak, Hard Maple | Red Oak, Hard Maple | Red Oak, Hard Maple, Yellow Birch | Red Oak, Hard Maple |
| Grades | Select & Better | Select & Better, Exclusive | Character | Tradition | Tradition |
| Description | <p>Select & Better: This floor offers a distinguished and even looking appearance with subtle color variation and natural shades. Presence of small sound knots and mineral streaks are very limited.</p> <p>Exclusive: Mostly even in appearance, this floor features a natural color variation with occasional darker shades. Small sound knots and mineral streaks are allowed in restricted size and numbers. Fine splits and checks are also possible in very limited number.</p> <p>Tradition: This floor features moderate to pronounced variation in color and natural shades. Natural characteristics such as sound knots, filled knots and mineral streaks may compliment this grade's appearance. Fine splits and checks may be present occasionally.</p> <p>Character: This floor displays all the natural characteristics of wood. Pronounced color variation, filled sound knots, mineral streaks, splits and checks are included in the distinct personality of this floor.</p> | | | | |

| CONSTRUCTION | Püre Series | Décor Series | Lodge Series | Essential Series | Classics Series |
|-------------------------|---|------------------|------------------|------------------|------------------|
| Type | Solid | Solid | Solid | Solid | Solid |
| Widths | - | - | - | 2 1/4" (57 mm) | - |
| | 4 1/4" (108 mm) | 3 1/4" (82.5 mm) | 3 1/4" (82.5 mm) | 3 1/4" (82.5 mm) | 3 1/4" (82.5 mm) |
| Length - Random Lengths | Min. 12", Max. 72" (Min. 305 mm, Max. 1,829 mm) | | | | |
| Edges | Micro-V on all 4 sides | | | | |
| Joint | Tongue and groove | | | | |
| Thickness | 3/4" (19 mm) | | | | |
| Relative Humidity | 35% - 55% | | | | |
| Fabrication | Harvested, designed and manufactured in Canada (Quebec) | | | | |

| FINISH | Püre Series | Décor Series | Lodge Series | Essential Series | Classics Series |
|---|--|-------------------|---------------------|------------------|------------------|
| Textures | Smooth | Smooth | Smooth (Hard Maple) | Smooth | Smooth |
| | - | - | Brushed (Red Oak) | - | - |
| Sheen (Gloss Level) | Ultra-Matte (10%) | Ultra-Matte (10%) | Ultra-Matte (10%) | Matte (20%) | Semi-Gloss (45%) |
| Alumina Finish with PermaClean® Antibacterial Characteristics | Finishing system made of aluminum oxide suspended in UV cured polyurethane | | | | |
| | Appearance and durability: Superior | | | | |
| | Gloss wear resistance and stain resistance: Superior | | | | |
| | Easy to maintain and to repair: Superior | | | | |
| | Formaldehyde, Solvent & Water: No added formaldehyde | | | | |
| Static Friction Coefficient ASTM D-2394-99 | Slippery resistance coefficient more than 0.5 | | | | |

| INSTALLATION, USAGE & WARRANTIES | | | | | |
|--|---|-----------------------------------|---------------------------------------|--|--|
| Installation | Levels: Main and upper floors | Methods: Nailed or stapled | Subfloors: Plywood or OSB 3/4" | | |
| Radiant Heat | Not compatible | | | | |
| Maintenance | Recommended hardwood flooring cleaning products | | | | |
| Uses | Residential | | | | |
| Warranties | Structural : Lifetime | | | | |
| (Please refer to the Installation Guide) | Wear-through finish: Residential 35 years | | | | |

| PRODUCT STANDARDS | | | | | |
|--------------------------------------|--|--|--|--|--|
| Formaldehyde Emission ASTM D6007-14 | Below limit of quantitation of 0.008 ppm | | | | |
| VOC Total ASTM-D-6670-01 | 0.003 ppm (depends on wood species) | | | | |
| Surface Burning ASTM-E84 | Classe 3 or C | | | | |
| R value | R 0.44 to 0.51 (depends on wood species) | | | | |
| Critical Radiant Flux ASTM-E-648-94a | 0.25 - 0.40 watt/cm ² (depends on wood species) | | | | |

| CERTIFICATIONS | | | | | |
|---------------------|---|--|--|--|--|
| LEED | Qualifies for LEED credits projects - Please refer to Eco-declaration VED16-1067-01 | | | | |
| CARB 93120 Phase II | Compliant | | | | |
| Lacey Act | Compliant | | | | |
| ISO 14001 | CERT-0120164 | | | | |

| PACKAGING | 2 1/4" (57 mm) | 3 1/4" (82.5 mm) | 4 1/4" (108 mm) |
|---------------------|--|--|--|
| Coverage per box | 20 ft ² (1.86 m ²) | 20 ft ² (1.86 m ²) | 17 ft ² (1.58 m ²) |
| Box size | 85 7/8" L x 9 9/16" W x 3 5/16" H (2,178 mm L x 243 mm W x 84 mm H) | 80 5/32" L x 10 7/16" W x 3 5/16" H (2,036 mm L x 265 mm W x 84 mm H) | 79 11/16" L x 9 7/32" W x 3 5/16" H (2,024 mm L x 234 mm W x 84 mm H) |
| Box weight | 56 - 59 lb (varies depending on species) | 56 - 59 lb (varies depending on species) | 56 - 59 lb (varies depending on species) |
| Boxes per pallet | 52 | 52 | 52 |
| Coverage per pallet | 1,040 ft ² (96.62 m ²) | 1,040 ft ² (96.62 m ²) | 884 ft ² (82.13 m ²) |
| Pallet size | 86" L x 38" W x 44" H (2,184.4 mm L x 965.2 mm W x 1,117.6 mm H) | 81" L x 41" W x 44" H (2,057.4 mm L x 1,041.4 mm W x 1,117.6 mm H) | 81" L x ~37" W x ~44" H (2,057.4 mm L x 939.8 mm W x 1,117.6 mm H) |

| RELATIVE SPECIES HARDNESS | | | |
|----------------------------|--------------------------------------|-----------------------------------|--|
| NWFA Janka | Red Oak: 1,290 lb - average hardness | Hard Maple: 1,450 lb - 12% harder | |
| Hardness Test (ASTM-D-143) | Yellow Birch: 1,260 lb - 2% softer | | |

Reference: Red Oak 1,290 lb* - 100%

*lb = Applied force in pounds

Customer service: 1 877 427 5144

April 2024

